

Quote Order Date _____

Job Ref./No. _____ Collection Delivery Date Required: _____

Company Name _____

Address _____

Postcode _____

Telephone: _____

Fax: _____

Delivery Address _____

Postcode _____

Sign* _____

Print _____

*Unsigned Orders cannot be processed

Order Taken by _____

Overall Width (mm) _____ Overall Height (mm) _____ Open in

Open out

***Including any Cills or Frame Extenders all viewed from the Outside**

Size Limitations: Each panel must be no larger than 1200mm wide & 100kg in weight, no smaller than 550mm with a Maximum height of up to 3000mm, subject to wind load deflection (No calculations made unless specified)

Configuration:

55mm Fully Rebated Threshold Total Number of Sashes Number of Doors Folding / Sliding to the **Right**

20mm Non-Weather Rated Threshold Number of Doors Folding / Sliding to the **Left** If Master Door is required please indicate **L / R** **L** **R**

Standard Single Colour Options:

RAL 9005 Black Matt

RAL 7016 Anthracite Grey Matt

RAL 9016 White High Gloss

Standard Dual Colour Options:

RAL 7016 Anthracite Grey Matt / RAL 9016 White High Gloss

RAL 9005 Black Matt / RAL 9016 White High Gloss

*RAL Inside: _____ / Colour: _____ High Gloss Semi-Gloss Matt

*RAL Outside: _____ / Colour: _____ High Gloss Semi-Gloss Matt

Marine Guarantee required please tick *For Marine environment applications please refer to disclaimer at the foot of page

The above will incur an additional colour set-up cost and extended lead times

Traffic Door Handle Black White Satin Silver Chrome

Non-Locking T Handle Black White Satin Silver Chrome

Locking T Handle Black White Satin Silver Chrome

Hinges and associated hardware to be black finish as standard

**only on configurations without a traffic door*

Drainage: Concealed Face None

Cill: 95mm 150mm 177mm 190mm No Cill

~~Adjustable Hinge Stacker: Yes No~~

Overall Cill Size _____ mm Cut To Size As Standard

28mm Glazing Bead: AW660 Square Bead

Glazed: Yes No Standard 28mm glazing is 4mm Tough K Softcoat + ARGON + 4mm Tough Optiwhite Swiss Black Spacer Bar

20mm Extender 40mm Extender Trickle Vent Qty _____ 4000m² trickle vents through 40mm to the head

Left / Right / Top Left / Right / Top

Additional Requirements:

e.g. Pas 24/Document Q

Please note: We cannot guarantee any product installed within 50 metres of the coast, source of pollution or 2 metres from a swimming pool against deterioration of profile or hardware. Any product fitted within 5000 metres of a hostile environment a recommended cleaning regime must be adhered to and recorded (please consult product guide). | Additional costs may be incurred, please advise on the environment if appropriate. | All frames are non-load bearing.